

SignFix 2 Sign Adhesive

► Description

- NovaSeal SignFix 2 is a new type of Elastomeric Polymer exhibiting extremely high adhesion coupled with excellent sealing properties, making it highly versatile for a vast range of applications. It is U.V. and weather resistant and is suitable for indoor and exterior use. It will even bond damp surfaces.
- NovaSeal SignFix 2 is a thixotropic, sag resistant adhesive/sealant staying in situ without movement and giving high initial bond to most substrate surfaces including, painted finishes. NovaSeal SignFix 2 is paintable wet-on-wet in under 30 minutes in most cases. Solvent and isocyanate free.

► Applications

- Ideal as a bonding medium and joint sealer in architectural signage exhibiting high strength, waterproof bonds remaining flexible in service. The crystal clear version is excellent for illuminated signage for perfect aesthetics without shadowing. Its neutral and odourless cure combined with anti-fungal and anti-microbial properties lend its use to bonding wall panels and trims in hospitals and clean room environment.

► Product features

- **Resin:** Silane Modified Polyether
- **Colour:** Crystal Clear/Transparent
- **Packaging Size:** 290ml cartridges

Curing system	By means of humidity
Curing speed	2.5 to 3 mm/24 hours at 23°C and 50% R.H
Number of components	1
Skin formation time	15 à 20 min. at 23°C and 50% R.H
Density	1.06 g/ml approx (ISO 1183) opaque: ca. 1.07 g/ml (ISO 1183)
Shore A hardness	35 (±5) (ISO-868)
Joint movement capacity	+/-20%
Modulus at 100% elongation	0.700 N/mm ² (ISO-8339-40)
Modulus at break	colours: 0.800 N/mm ² (ISO-8339-40)

Elongation at break	150% (ISO-8339-40)
Shearing stress	2.1 N/mm ² (DIN 53283)
Solvent content	0%
Isocyanate content	0%
Dry matter content	100% approx.
Processing temperature	+5°C to +40°C (do not process below +5°C)
Temperature stability	-40°C to +90°C
Moisture resistance	Very good
Frost stability	Not sensitive to frost

NovaSeal SignFix 2 remains flexible and resists vibration making it ideal for bonding and sealing all types of vehicle, caravan and truck bodies including stiffener bars and side panels. It lends its use well for electrical, heating and ventilation, air-conditioning and most types of equipment.

HEALTH & SAFETY IN USE

Observe good housekeeping practices. Read Health & Safety Sheets.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.